

TECHNICAL SPECIFICATION
TRACK SPEAKER
MODEL V-1014B (-BK, -GY, -W)



FEATURES:

- High Gloss Finish
- Black (-BK) Gray (-GY) or White (-W) Finishes
- Omni-Directional Mounting
- High Fidelity Full Range Speaker



DESCRIPTION:

Fashionable track style speaker that may be installed on wall or ceiling. Track speakers are a stylish answer for providing paging and background music in offices, restaurants and lobbies. The speaker utilizes a full range high fidelity 5-inch speaker and is filled with damping material to minimize vibrations. Effortless aiming of the speaker is accomplished by loosening two knobs.

These track speakers are available in white, black or gray high gloss finishes. A volume control is provided for easy adjustments of audio levels.

Specifications

SPEAKER ELEMENT

Cone Diameter: 5" (12.7 cm)
Voice Coil Impedance: 8 ohms

INPUTS

Impedance: > 600 ohms nominal
Signal Level: -10 dBm line level

OUTPUT

Rating: 100 dB @ 4' (1.22 m)

FREQUENCY RESPONSE

70 Hz - 16 kHz

POWER REQUIREMENTS

300 mA @ -24 Vdc

HOUSING AND FINISH

Aluminum tube construction with white, black or gray powder coat finish. A 6-foot chain with black finish is included for hanging the speaker.

ENVIRONMENT

Temperature: -4 to +13 °F (-20 to +55°C)
Humidity: 0-95% Non-Condensing

DIMENSIONS AND WEIGHT

8.8 "H x 5.8 "Dia (22.352 cm x 14.732 cm)
Weight: 3.1 lbs (1.4 kg)
Shipping Weight: 5.5 lbs (2.475 kg)

ARCHITECTS' AND ENGINEERS

The Model V-1014B Track Speaker shall consist of a speaker baffle assembly designed to be mounted on a wall.

The speaker housing shall be 8.8 "L x 5.8 "Dia (22.352 cm x 14.732 cm). The speaker shall weigh 3.1 lbs (1.4 kg). The speaker housing shall be constructed of aluminum tubing and finished in a white, gray or black epoxy powder coat paint.

The frequency response shall be 70 Hz to 16 kHz. The output shall be 100 db, at 4 feet. The amplifier shall operate on a -24 Vdc nominal power supply. Operating current shall be 300 mA at -24 Vdc. Operating temperature shall be -4 to +131°F (-20 to +55°C) Humidity range shall be 0-95%, non-condensing.

A screwdriver adjustable volume control shall be provided at the center of the grille.

Warranty information may be found on our website at www.valcom.com/warranty.