

TECHNICAL SPECIFICATION
SLIMLINE ONE-WAY SPEAKER
MODEL V-1042



FEATURES:

- Utilizes Standard CAT 3, 5, Or 6 Cable
- Removable Cloth Covered Grille
- Built-In Hanger
- High Density Polypropylene Enclosure
- Voice and Music Reproduction Quality



DESCRIPTION:

Contemporary designed wall speaker for areas that require a stylish appearance. Used for background music and voice paging, the thick walled, high density polypropylene enclosure minimizes vibrations. Utilizing the built-in hanger, this speaker may be conveniently mounted on the wall. The speaker is available in black, white, and gray with a color coordinated cloth grille.

Specifications

SPEAKER ELEMENT

Cone Diameter: 5.0" (12.7 cm)
Voice Coil Impedance: 45 ohms

INPUTS

Impedance: > 600 Ohms nominal
Signal Level: -10 dBm line level

OUTPUT

Rating: > 93 dB @ 4' (1.22 m)

FREQUENCY RESPONSE

95 Hz to 16 kHz

HOUSING AND FINISH

High density polypropylene in black, white, or gray with color coordinated cloth grille.

ENVIRONMENT

Temperature: -4 to +131°F (-20 to +55°C)
Humidity: -0-95% Non-Condensing

DIMENSIONS AND WEIGHT

7.0 "H x 10.3 "W x 3.4 "D (17.78 cm x 26.162 cm x 8.636 cm)
Weight: 2.8 lbs (1.27 kg) **Shipping Weight:** 3.5 lbs (1.575 kg)

ARCHITECTS' AND ENGINEERS

The Slimline One-Way Wall Speaker, Model V-1042 shall be constructed of a high-density polypropylene with a removable color coordinated cloth covered grille. The unit shall include a 45-ohm speaker, amplifier, and volume control.

The amplifier shall have a frequency response of 95 Hz to 16 kHz. The amplifier shall operate on a -24 Vdc nominal, positive ground power supply. Operating current shall be 50 mA at -24 Vdc. Operating temperate shall be -4 to+131°F (-0 to +55°C). The wall speaker shall have an integral hanger molded in the cabinet.

The dimensions shall be 7.0 "H x 10.3 "W x 3.4 "D (17.78 cm x 26.162 cm x 8.636 cm). The weight shall be 2.8 lbs (1.27 kg).

Warranty information may be found on our website at www.valcom.com/warranty.