

TECHNICAL SPECIFICATION
DESKTOP/WALL SPEAKER
MODEL V-763



FEATURES:

- Utilizes Standard CAT 3, 5, Or 6 Cable
- Sits on Desktop or Mounts on Wall
- Externally Accessible Volume Control
- Attractive White, Gray or Black Finish



DESCRIPTION:

Desktop or wall surface mounted speaker assembly complete with speaker, amplifier and built-in volume control.

Specifications

INPUTS

Impedance: 600 Ohms nominal
Signal Level: -10 dBm line level

OUTPUT

Rating: > 93 dB @ 4' (1.22 m)

FREQUENCY RESPONSE

220 Hz to 10 kHz

POWER REQUIREMENTS

50 mA @ -24 Vdc

HOUSING AND FINISH

Available in Black, Gray or White

DIMENSIONS AND WEIGHT

3.9 "H x 5.1 "W x 3.2 "D (9.906 cm x 12.954 cm x 8.128 cm)

Weight: 0.7 lbs (0.32 kg)

Shipping Weight: 0.8 lbs (0.36 kg)

ARCHITECTS' AND ENGINEERS

The Desktop/Wall Speaker, Model V-763 shall consist of a 45-ohm speaker, amplifier with 600-ohm input impedance and volume control. The speaker, housing and hardware shall be electrically and acoustically matched for a frequency response of 220 Hz to 10 kHz.

The speaker element shall be cone type. Voice coil impedance shall be 45-ohm.

The amplifier shall have a frequency response of 220 Hz to 10 kHz. Amplifier audio input impedance shall be > 600 ohm. Amplifier audio input shall be -10 dBm line level. The amplifier shall operate on a -24 Vdc nominal, positive ground power supply. Operating current shall be 50 mA at -24 Vdc.

A volume control shall be provided on the unit. This volume control shall be externally accessible, making it possible to adjust volume level of speaker without tools.

The V-763 shall be available in black, gray or white.

Maximum dimensions of the housing shall be 3.9 "H x 5.1 "W x 3.2 "D (9.906 cm x 12.954 cm x 8.128 cm). Approximate weight is 0.7 lbs (0.32 kg).

Warranty information may be found on our website at www.valcom.com/warranty.