Technical Specifications

V-763 Desktop/Wall Speaker

- Utilizes standard CAT 3, 5, or 6 cable
- Paging, emergency alerts and tones
- One-way paging
- Sits on desktop or mounts on wall
- Multiple color options
- Quick and easy installation
- High quality audio
- Indoor use only

Self-amplified
One-way

Description:
The V-763 Desktop/Wall Speaker is the perfect choice for high quality voice paging and emergency alerts for indoor areas. It is self-standing or can be mounted on a wall as a mini speaker.

SPECIFICATIONS

INPUT
Impedance: > 600 Ohms nominal
Signal Level: -10 dBm line level l

OUTPUT
Rating: > 93 dB @ 4ft (1.22m)

FREQUENCY RESPONSE
220 Hz to 10 kHz

POWER REQUIREMENTS
50 mA @ -24 Vdc

ENVIRONMENT
Temperature: -4 to +131°F (-20 to +55°C)
Humidity: 0 to 95% non-condensing

HOUSING AND FINISH
Black, white or gray

MOUNTING
Desk or wall mountable

DIMENSIONS AND WEIGHT
3.90in H x 5.10in W x 3.20in D
(9.90cm x 12.90cm x 8.10cm)
Weight: 0.70lbs (0.32kg)
Shipping Weight: 2.60lbs (1.17kg)

ARCHITECTS AND ENGINEERS

The Desktop/Wall Speaker, model V-763 shall consist of a speaker, amplifier and volume control. The speaker, housing and hardware shall be electrically and acoustically matched for a frequency response of 220 Hz to 10 kHz.

The V-763 amplifier shall have a frequency response of 220 Hz to 10 kHz. Amplifier audio input impedance shall be > 600 Ohm. Amplifier audio input shall be -10 dBM line level. The V-763 amplifier shall operate on a -24 Vdc nominal, positive ground power supply. Operating current shall be 50 mA at -24 Vdc. Operating temperature shall be -4 to +131 °F (-20 to +55 °C).

The V-763 Desktop/Wall Speaker shall be available in black, gray or white. The V-763 volume control shall be provided on the unit. The externally accessible volume control shall be adjusted with the knob on the front of the housing. The V-763 shall be suitable for indoor applications.

The maximum dimensions shall be: 13.90in H x 5.10in W x 3.20in D (9.90cm x 12.90cm x 8.10cm). Weight shall be approximately: 0.70lbs (0.32kg).

Warranty information may be found on our website at www.valcom.com/warranty.