

Technical Specifications

VIP-410A-IC InformaCast® IP Metal Wall Speaker

- InformaCast® compliant
- PoE (IEEE 802.3af)
- Paging, emergency alerts, and tones
- One-way paging
- High-quality audio
- Quick and easy installation
- Indoor use only



*InformaCast compliant
One-Way*

Description:

The VIP-410A-IC InformaCast IP Metal Wall Speaker is a sleek, modern design made of steel that provides excellent voice and music quality for any office. The color of the enclosure can easily be changed to match any interior décor and is easily installed.

SPECIFICATIONS

SPEAKER ELEMENT

Voice coil impedance: 45 Ohms

AUDIO OUTPUT

Rating: > 96 dB @ 4ft (1.22 m)

FREQUENCY RESPONSE

80 Hz to 15 kHz

NETWORK

10/100 Mbps Ethernet port
Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup
Time and date synchronization using NTP

POWER REQUIREMENTS

Power over Ethernet (POE) 802.3af compatible

INFORMACAST CONFIGURATION METHODS

SLP (Service Location Protocol)
Static Configuration

AUDIO CODECS

G.711 u-law, others

7.40lbs (3.33kg)

PROTOCOLS

IETF SIP (RFC3261)
IETF IGMP version 3 (RFC3376)
IETF RTP (RFC1889)
IETF RFC2833

ENVIRONMENT

Temperature: +32 to +104 °F (0 to +40 °C)

Humidity: 0 to 85% non-precipitating

HOUSING AND FINISH

Steel with a durable powder coated gray finish and black cloth grille

DIMENSIONS AND WEIGHT

10.13in H x 12.31in W x 4.63in D
(25.73cm x 31.27cm x 11.76cm)

Weight: 4.25lbs (1.93kg).

Shipping Weight: 7.40lbs (3.33kg)

2022 Rev. 1.9.1.2

Technical Specifications

ARCHITECTS AND ENGINEERS

The InformaCast IP Wall Speaker, model VIP-410A-IC, shall be InformaCast compliant. The VIP-410A-IC shall enable paging access to a single location over an IP-based LAN/WAN. The VIP-410A-IC speaker levels are electrically adjusted during setup.

Power shall be provided to the VIP-410A-IC via a Power over Ethernet (PoE) switch meeting the 802.3af specification. The VIP-410A-IC shall automatically acquire an IP address (using DHCP) and shall connect to the InformaCast server when connected to the network and powered up. Information specific to the application shall need to be programmed into the InformaCast server.

The VIP-410A-IC enclosure shall be constructed of steel with a durable gray powder coated finish. The color of the VIP-410A-IC enclosure shall be easily changed to match any decor. A detachable black cloth grille shall be included. The VIP-410A-IC shall be suitable for indoor applications.

Maximum dimensions shall be: 10.13in H x 12.31in W x 4.63in D (25.73cm x 31.27cm x 11.76cm). Weight shall be approximately 4.25lbs (1.93kg).

Warranty information may be found on our website at www.valcom.com/warranty.