

Technical Specifications

VIP-9895-IC InformaCast® IP Emergency Call Station

- InformaCast® compliant
- PoE (IEEE 802.3af)
- Compatible with most modern IP telephone systems
- Call-In identification for precise location
- Available in blue (-B), yellow (-Y), red (-R) gray (-G) stainless steel (-SS)
- High-intensity blue LED flashing light in active mode
- Indoor/outdoor use



*InformaCast compliant
Vandal-resistant
Surface mount*

Description:

The VIP-9895-IC IP Emergency Call Station provides one-way or two-way communication to multiple answer locations. By pressing a single button, a two-way communication is initiated between an individual to the information desk or security personnel. As an endpoint, the V-9895-IC is capable of broadcasting important emergency information. The VIP-9895-IC integrates with multiple SIP manufactured compatible devices. The VIP-9895-IC is an excellent choice for building entrances and dormitories, hallways, parking lots/garages and public transit centers.

SPECIFICATIONS

SPEAKER ELEMENT

3.50in dia

Voice coil impedance: 45 Ohm

AUDIO OUTPUT

Rating: > 100 dB @ 4ft (1.22 m) on axis

CALL SWITCH

Single Pole Momentary Contact

POWER REQUIREMENTS

Power over Ethernet (POE) 802.3af compatible

NETWORK

10/100 Mbps Ethernet port

Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup

Time and date synchronization using NTP

PROTOCOLS

IETF SIP (RFC3261)

IETF IGMP version 3 (RFC3376)

IETF RTP (RFC1889)

IETF RFC2833

AUDIO CODECS

G.711 u-law, others

INFORMACAST CONFIGURATION METHODS

SLP (Service Location Protocol)

Static Configuration

ENVIRONMENT

Temperature: +32 to +104 °F (0 to +40 °C)

Humidity: 0 to 85% non-precipitating

HOUSING AND FINISH

Enclosure: Structural grade steel

Finish: Safety yellow, safety blue, light gray, stainless steel

Grille: Brushed stainless steel

Hardware: Corrosion proof, vandal resistant

DIMENSIONS AND WEIGHT

32.15in H x 9.90in W x 8.00in D

(81.66cm x 25.10cm x 20.30cm)

Weight: 34.20lbs (15.39kg)

Shipping Weight: 39.75lbs (18.10kg)

MOUNTING

Surface mount

2022 Rev. 1.9.1.9

Technical Specifications

ARCHITECTS AND ENGINEERS

The IP Emergency Wall Mount Call Station, model VIP-9895-IC, shall be InformaCast compliant. VIP-9895-IC shall provides emergency communication to any SIP telephone, InformaCast intercom or to a Valcom IP Gateway. At the time of activation, the high intensity blue LED shall change from beacon mode to flash mode. The LED shall continue to flash until the call is terminated. .

Power shall be provided to the VIP-9895-IC via a Power over Ethernet (PoE) switch meeting the 802.3af specification. Setup of the VIP-9895-IC shall automatically acquire an IP address (using DHCP) and connect to the InformaCast server when connected to the network and powered up. Information specific to the application shall need to be programmed into the InformaCast server.

The VIP-9895-IC Vandal Resistant IP Handsfree Emergency Call Station shall be designed for surface or pole mounting. The VIP-9895-IC Vandal Resistant IP Handsfree Emergency Call Station enclosure shall be constructed of structural grade steel with a yellow, blue, red, gray or stainless steel finish. The grille shall be constructed of brushed stainless steel. Corrosion-proof vandal-resistant hardware shall be included. The VIP-9895-IC shall be suitable for indoor and outdoor applications.

Maximum dimensions shall be: 32.15in H x 9.90in W x 8.00in D (81.66cm x 25.10cm x 20.30cm). Weight shall be approximately 34.20lbs (15.39kg).

Warranty information may be found on our website at www.valcom.com/warranty.