



TALKBACK WALL SPEAKER MODEL V-WTGY

FEATURES:

- BUILT-IN VOLUME SETTINGS
- WIDE SOUND DISPERSION
- ELECTRICALLY, ACOUSTICALLY MATCHED PARTS
- ATTRACTIVE GRAY METAL CABINET



DESCRIPTION:

Wall surface mounted speaker unit complete with 45 ohm speaker, volume settings and sloped baffle.

Specifications:	
<p>SPEAKER ELEMENT Cone Diameter: 8.0" Voice Coil Impedance: 45 ohm</p> <p>FREQUENCY RESPONSE 60 Hz to 12 kHz</p> <p>POWER RATING 12 Watts</p>	<p>HOUSING AND FINISH The baffle is constructed of gray painted steel with a black grille cloth.</p> <p>ENVIRONMENT Temperature: -20 to +55°C (-4 to +131 °F) Humidity: 0-95% Non-Condensing</p> <p>DIMENSIONS AND WEIGHT 9.6 "H x 11.5 "W x 4.2 "D (24.384 cm x 29.21 cm x 10.668 cm) Weight: 4.5 lbs (2.025 kg) Shipping Weight: 5.0 lbs 2.25 kg)</p>

MultiPath is a registered Trademark of Valcom, Inc.

Valcom, Inc. 5614 Hollins Road Roanoke, Virginia 24019 Phone: 540-563-2000 Fax: 540-362-9800
E-Mail: info@valcom.com www.valcom.com



TALKBACK WALL SPEAKER MODEL V-WTGY

Technical Specification

ARCHITECTS' AND ENGINEERS

The Wall Speaker, Model V-WTGY, shall consist of a speaker, volume settings and sloped baffle. The speaker, housing and hardware shall be electrically and acoustically matched for a frequency response of 60 Hz to 12 kHz.

The speaker shall be 8" (20.32 cm) in diameter and have a ceramic magnet weighing 5 ounces. The impedance of the speaker shall be 45 Ohm. The voice coil shall be .75" (1.91 cm) in diameter. Voice coil impedance shall be 45 ohm. Operating temperature shall be -20 to + 55 °C (-40 to + 131 °F).

The baffle shall be constructed of gray painted steel with a black cloth grille.

Maximum dimensions of the housing shall be 9.6 "H x 11.5 "W x 4.2 "D (24.384 cm x 29.21 cm x 10.668 cm). Approximate weight is 4.5 lbs (2.025 kg).

Limited Warranty

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Clarity indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened.
(A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Clarity are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs
(*major repairs will be subject to additional charges for parts and labor*).

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Valcom be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.

MultiPath is a registered Trademark of Valcom, Inc.

Valcom, Inc. 5614 Hollins Road Roanoke, Virginia 24019 Phone: 540-563-2000 Fax: 540-362-9800
E-Mail: info@valcom.com www.valcom.com