



# 2' x 2' TALKBACK LAY-IN CEILING SPEAKER MODEL V-CTLA-2

## Technical Specification

### FEATURES:

- EASY LAY-IN MOUNTING
- VOLUME SETTINGS
- SCUFF RESISTANT PERFORATED GRILLE
- DURABLE WHITE ACRYLIC BAKED ENAMEL FINISH
- INTEGRAL BACKBOX WITH THREE HOUR BURN RATING



### DESCRIPTION:

This inconspicuous Lay-in Speaker can be installed in suspended ceilings in a minute. The speaker provides excellent music and voice reproduction. The integral backbox has a three hour burn test rating (UL181) and the rugged lightweight construction eliminates the need for support bars. The speakers white perforated grille blends into the ceiling by providing the appearance of a standard air return. The speaker assembly features a perforated steel grill finished with a durable white baked on acrylic enamel finish, and a 8" full range speaker with volume settings.

Specifications:	
<p><b>SPEAKER</b> 8" (20.32 cm) Speaker</p> <p><b>MAGNET WEIGHT</b> 5 oz.</p> <p><b>MAGNET MATERIAL</b> Ceramic</p> <p><b>VOICE COIL</b> 45 ohm 3/4" (.34 cm) dia.</p> <p><b>SOUND PRESSURE LEVEL</b> 95 dB at 1 Meter on Axis With 1 Watt Input at 1 kHz</p> <p><b>FREQUENCY RESPONSE</b> 70 Hz to 17 kHz</p> <p><b>POWER RATING</b> 5 Watts Continuous</p>	<p><b>HOUSING AND FINISH</b> Steel housing with a white baked on acrylic enamel Finish</p> <p><b>ENVIRONMENT</b> Temperature: 0 to 50 °C (32 to 122 °F)</p> <p><b>DIMENSIONS AND WEIGHT</b> 23.75 "L x 23.75 "L x 3.75 "D ( 60.325 cm x 60.325 cm x 9.525 cm) Weight: 5.5 lbs (2.48 kg) Shipping Weight: 14.0 lbs ( 6.3 kg) Packaged 2 per box</p>

MultiPath is a registered Trademark of Valcom, Inc.

Valcom, Inc. 5614 Hollins Road Roanoke, Virginia 24019 Phone: 540-563-2000 Fax: 540-362-9800  
E-Mail: info@valcom.com www.valcom.com



# 2' x 2' TALKBACK LAY-IN CEILING SPEAKER MODEL V-CTLA-2

## Technical Specification

---

### ARCHITECTS' AND ENGINEERS

The Model V-CTLA-2 Lay-in Ceiling Speaker shall consist of a white two foot by two foot perforated grille, a speaker and integral backbox. The volume setting is located in the back of the enclosure.

The speaker shall be 8" (20.32 cm) in diameter and have a 5 oz. ceramic magnet. The 8" speaker cone material shall be paper. The speaker impedance shall be 45 ohms. The diameter of the voice coil shall be 3/4" (.34 cm) diameter. The speaker shall be capable of handling 5 watts continuous power. Sound pressure level at 1 meter on axis with a 1 watt input shall be 95 dB. The frequency response shall be 70 Hz to 17 kHz.

The baffle shall be constructed with a single piece of perforated steel with a white baked on acrylic enamel finish. The backbox meets or exceeds A.S.T.M. E84 flame and smoke test and has a three hour burn rating (UL181).

Maximum dimensions of the grill shall be: 23.75 "L x 23.75 "L x 3.75 "D (60.325 cm x 60.325 cm x 9.525 cm). Weight shall be approximately 5.5 lbs (2.48 kg).

### Limited Warranty

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Clarity indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened.  
(A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Clarity are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs  
(*major repairs will be subject to additional charges for parts and labor*).

**This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Valcom be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.**

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.

---

MultiPath is a registered Trademark of Valcom, Inc.

Valcom, Inc. 5614 Hollins Road Roanoke, Virginia 24019 Phone: 540-563-2000 Fax: 540-362-9800  
E-Mail: [info@valcom.com](mailto:info@valcom.com) [www.valcom.com](http://www.valcom.com)