# SURFACE MOUNT DOOR SPEAKER MODEL V-1074

### **FEATURES:**

- UTILIZES STANDARD CAT 3, 5, OR 6 CABLE
- 45 OHM INPUT IMPEDANCE
- WEATHER RESISTANT
- CALL SWITCH BUTTON
- SCREW TERMINALS FOR ALL CONNECTIONS

| - | - | -    |    |
|---|---|------|----|
| - | _ | -    |    |
| - | _ | _    | -  |
| - |   |      |    |
|   |   |      |    |
|   |   | -    |    |
|   |   | 0    | 18 |
|   |   | 1000 |    |

#### **DESCRIPTION:**

Durable gray plastic door plate speaker with call button. The unit provides handsfree talkback capability from an outside entry or doorway when used with the Valcom Door Entry Management and Intercom Systems. The unit features a water resistant 2-inch speaker and corrosion resistant hardware.

| Specifications:                         |                                                                                                                                                             |  |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| SPEAKER<br>45 ohm                       | <b>ENVIRONMENT</b><br>Suitable for Indoor or Outdoor Installations                                                                                          |  |
| SWITCH<br>Single Pole Momentary Contact | <b>DIMENSIONS AND WEIGHT</b><br>5.5 "H x 4 "W x 1.125 "D (13.97 cm x 10.16 cm x 2.8575 cm)<br>Weight: 0.5 lbs (.23 kg)<br>Shipping Weight: 0.7 lbs (.32 kg) |  |
|                                         | MOUNTING<br>Surface Mount                                                                                                                                   |  |

800.825.2661 | 540.563.2000 | Valcom.com | is@valcom.com | 5614 Hollins Road, Roanoke, VA 24019 USA



## **ARCHITECTS' AND ENGINEERS**

The Talkback Door Plate Speaker, Model V-1074, shall be a weather resistant speaker assembly for use with handsfree talkback control units. It shall have a voice coil rating of 45 Ohms. The surface mount assembly shall be constructed of gray plastic. It shall have a call button for signaling.

Dimensions shall 5.5 "H x 4 "W x 1.125 "D (13.97 cm x 10.16 cm x 2.8575 cm) and the unit shall weigh 0.5 lb (0.23 kg).

#### LIMITED WARRANTY

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of nor-mal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the re-placement, repair or refund of any such defective device within the warranty period, provided that:

- 1. inspection by Valcom, Inc. indicates the validity of the claim,
- 2. the defect is not the result of damage, misuse, or negligence after the original shipment,
- 3. the product has not been in any way repaired by others and that factory sealed units are unopened (A service charge plus parts and labor will be applied to units defaced or physically damaged).
- 4. freight charges for the return of products to Valcom, Inc. are prepaid,
- 5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs (major repairs will be subject to additional charges for parts and labor)

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event, shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.

800.825.2661 | 540.563.2000 | Valcom.com | is@valcom.com | 5614 Hollins Road, Roanoke, VA 24019 USA