TECHNICAL SPECIFICATION TALKBACK WALL SPEAKER MODEL V-1063A

FEATURES:

- Utilizes Standard CAT 3, 5, Or 6 Cable
- Used with Talkback Page Controls
- Electrically, Acoustically Matched Parts
- Attractive Walnut Finish

DESCRIPTION:

Wall surface mounted speaker assembly complete with 45-ohm speaker, sloped baffle and mounting bracket.

Specifications

SPEAKER ELEMENT

Cone Diameter: 8.0" (20.32 cm) Voice Coil Impedance: 45 Ohm

FREQUENCY RESPONSE:

80 Hz to 15 kHz

SPEAKER POWER RATING:

12-Watts

ENVIRONMENT

Temperature: -4 to +131 °F (-20 to +55°C) **Humidity**: 0-95% Non-Condensing

HOUSING AND FINISH

Baffle constructed of .5" (1.27 cm) particle board, covered with walnut vinyl with matching brown cloth grille.

DIMENSIONS AND WEIGHT

9.6 "H x 11.5 "W x 4.2 "D (24.384 cm x 29.21 cm x 10.668 cm) Weight: 4.0 lbs (1.84 kg) Shipping Weight: 4.5 lbs (2.025 kg)

ARCHITECTS' AND ENGINEERS

The Wall Speaker, Model V-1063A shall consist of a 45-ohm speaker and sloped baffle. The speaker, housing and hardware shall be electrically and acoustically matched for a frequency response of 80 Hz to 15 kHz. The speaker element shall be cone type with 5 oz (142 g) ceramic magnet. Diameter of speaker cone shall be 8.0" (20.32 cm) with 2.0" (5.08 cm) whizzer cone. Voice coil diameter shall be .75" (1.91 cm). Voice coil impedance shall be 45-ohm. Speakers utilizing an 8-ohm voice coil are not acceptable. Operating temperature shall be -4 to + $131^{\circ}F$ (-20 to + $55^{\circ}C$).

The baffle shall be constructed of .5" (1.27 cm) particle board covered with simulated walnut vinyl with brown grille cloth.

Maximum dimensions of the housing shall be 9.6 "H x 11.5 "W x 4.2 "D (24.38 cm x 29.21 cm x 10.67 cm). Approximate weight is 4.0 lbs (1.8 kg).

Warranty information may be found on our website at www.valcom.com/warranty.



