TECHNICAL SPECIFICATION TALKBACK METAL WALL SPEAKER MODEL V-WTGY

FEATURES:

- Built-In Volume Settings
- Wide Sound Dispersion
- Electrically, Acoustically Matched Parts
- Attractive Gray Metal Cabinet



DESCRIPTION:

Wall surface mounted speaker unit complete with 45-ohm speaker, volume settings and sloped baffle.

Specifications

POWER RATING

12-Watts

SPEAKER ELEMENT Cone Diameter: 8.0" (20.32 cm) Voice Coil Impedance: 45-ohm

FREQUENCY RESPONSE 60 Hz to 12 kHz

HOUSING AND FINISH

Baffle constructed of steel with a durable powder coated gray finish with black cloth grille.

ENVIRONMENT

Temperature: -4 to +131°F (-20 to +55°C) **Humidity**: 0-95% Non-Condensing

DIMENSIONS AND WEIGHT

10.13 "H x 12.31 "W x 4.63 "D (25.7302 cm x 31.2674 cm x 11.7602 cm) Weight: 4.25 lbs (1.91 kg) Shipping Weight: 5.2 lbs (2.34 kg)

ARCHITECTS' AND ENGINEERS

The Wall Speaker, Model V-WTGY, shall consist of a speaker, volume settings and sloped baffle. The speaker, housing and hardware shall be electrically and acoustically matched for a frequency response of 60 Hz to 12 kHz.

The speaker shall be 8" (20.32 cm) in diameter and have a ceramic magnet weighing 5 ounces. The impedance of the speaker shall be 45 Ohm. The voice coil shall be .75" (1.91 cm) in diameter. Voice coil impedance shall be 45 ohm. Operating temperature shall be -40 to + 131° F (-20 to + 55° C).

The baffle shall be constructed of gray painted steel with a black cloth grille.

Maximum dimensions of the housing shall be 10.13" (25.73 cm) H x 12.31" (31.27 cm) W x 4.63" (11.75 cm) D. Approximate weight is 4.25 lbs (1.91 kg).

Warranty information may be found on our website at www.valcom.com/warranty.