

FEATURES:

- UTILIZES STANDARD CAT 3, 5, OR 6 CABLE
- STURDY STEEL HOUSING
- WATER-RESISTANT SPEAKER
- TAMPER-RESISTANT SCREWS



DESCRIPTION:

Surface mount speaker assembly, designed to be used in harsh environments. The speaker assembly features a steel housing, a built-in amplifier, an interior security screen, and tamper resistant screws.

Specifications:

SPEAKER

Voice Coil Impedance: 45 ohms
Diameter: 5.10"
Magnet Weight: 10 oz
Magnet Material: Ceramic

SPEAKER/AMPLIFIER

Frequency Response: 200 Hz to 8 kHz
Output Power: 1 Watt
SPL: > 95 dB @ 4'

AMPLIFIER

Power Rating: 1 Watt
Operating Voltage: -24 Vdc
Current Consumption: 50 mA

HOUSING AND FINISH

Steel housing finished with white epoxy powder. Includes tamper-resistant screws and steel security screen to prevent objects from penetrating speaker.

DIMENSIONS AND WEIGHT

8.5 "Dia. x 5.1 "D (21.59 cm x 12.954 cm)
 Weight: 4.8 lbs (2.18 kg)
 Shipping Weight: 5.5 lbs (2.48 kg)

MOUNTING

Mounts to standard 4-inch square or octagon shaped electrical box or may be fastened directly to wall or ceiling.

ARCHITECTS' AND ENGINEERS

The vandal resistant amplified speaker, Model V-9010-W, shall include a speaker, amplifier, volume control and steel housing. The speaker assembly, amplifier module, housing and hardware shall be electrically and acoustically matched for a frequency response of 200 Hz to 8 kHz.

The speaker element shall be cone type with 10 oz (284 g) ceramic magnet. Diameter of speaker cone shall be 5.10".

Voice coil impedance shall be 45 ohms.

The amplifier shall have a frequency response of 200 Hz to 8 kHz. Rated output shall be 1 watt. The amplifier shall operate on a -24 Vdc nominal, positive ground power supply. Operating current shall be 50 mA at -24 Vdc.

The housing shall be constructed of 18-gauge steel with a baked on white powder coat urethane finish. A screen made of 24-gauge steel shall be included to prevent sharp objects from penetrating the speaker.

The maximum dimensions shall be 8.5 "Dia. x 5.1 "D (21.59 cm x 12.954 cm). Weight shall be approximately 4.8 lbs (2.18 kg).

LIMITED WARRANTY

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the re-placement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened (A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs (major repairs will be subject to additional charges for parts and labor)

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event, shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.